




3. OPRACOVANÉ PLOCHY 1x NÁTER ZINKOVOU FARBOU.
2. NA VRTANÝCH OTVOROCH ODSTRÁNIŤ OSTRÉ HRANY 0,3x45°.
1. HMOTNOSŤ: 0,447 kg.

|                                                               |                             |                                                                                                                                                                                                                                                                                          |                                 |                         |
|---------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------------------|
| GENERAL TOLERANCES COMPLY WITH<br><b>STN ISO 2768 - mK</b>    |                             | THIS DRAWING IS THE PROPERTY OF DELTA DEFENCE a.s. IT IS NOT TO BE COPIED OR DUPLICATED IN ANY MANNER, AND SHALL NOT BE SUBMITTED TO OUTSIDE PARTIES FOR EXAMINATION WITHOUT OUR KNOWLEDGE AND CONSENT. IT SHALL BE USED AS A MEANS OF REFERENCE TO WORK FURNISHED BY THIS COMPANY ONLY. |                                 |                         |
| DRAWN BY<br><b>ZG</b>                                         | DATE<br><b>20. 11. 2024</b> | <b>DELTA DEFENCE a.s. BRATISLAVA</b>                                                                                                                                                                                                                                                     |                                 |                         |
| MATERIAL<br><b>OCEL, ZN</b>                                   |                             | FIRST ANGLE PROJECTION<br>                                                                                                                                                                            | SCALE:<br><b>1:1</b>            | SHEET:<br><b>1 OF 1</b> |
| SEMI-PRODUCT<br><b>EMC50 BG, R15613B105<br/>BOSCH+REXROTH</b> |                             | DESCRIPTION<br><b>PÄTKA-ÚPRAVA</b>                                                                                                                                                                                                                                                       |                                 |                         |
| REFERENCE<br><b>KS4A-45.0100</b>                              |                             | SIZE<br><b>A4</b>                                                                                                                                                                                                                                                                        | PART NO.<br><b>KS4A-45.0105</b> | REVISION                |

# VYROBA - KS4A-45.0105\_

Obj: BE300626 DielID: 59



1. Rezanie (akost MC50 BG R15613B105, pozn: BOSCH+REXROTH)
2. Frezovanie
3. Zamocnik
4. Lakovanie (pozn: zinok)